



## TECHNICAL DATA SHEET

### RLT CLEARMOULD FIRST RESPONSE SPRAY

#### DESCRIPTION

RLT CLEARMOULD FIRST RESPONSE SPRAY for walls and ceilings is an initial holding treatment to kill surface mould until the full MGC 3 Stage System can be applied to eradicate the problem. The material is spray applied, from approximately 20-30cm away, to the affected areas. Allow the foam 30 to 60 seconds to take full effect. Wipe clean with a cloth or sponge to remove the residues.

Before you start.

- Read and follow SDS, TDS and label instructions
- Mix all products as recommended thoroughly before use
- Always use the same batch number on the same job
- Check product - MGC will not accept any discrepancies arising after use
- Where necessary filter the product immediately before use
- Reduce chances of spillage by replacing container lids after use

If in any doubt speak to MGC's Technical Service Department on 01372 743334.

#### PREPARATION

All surfaces to be dry, free from loose and flaking material. Special precautions should be taken during surface preparation of pre1960's paint surfaces over wood and metal as they may contain harmful lead.

Ensure there is a physical barrier to prevent contact by unprotected persons and animals until treated surfaces are dry.

This material and its container **MUST BE DISPOSED OF IN A SAFE WAY**. When using do not eat, drink or smoke. Prevent any surface run-off from entering drains. Dangerous to fish and other aquatic life. Do not contaminate **WATERCOURSES**. Remove or cover fish tanks and bowls **BEFORE APPLICATION**.

#### APPLICATION

Attach trigger spray head. Spray affected surfaces from approximately 20-30cm away. Allow to take effect for 30 seconds to a minute. Wipe clean with a cloth or sponge lightly, scrub if necessary to remove contaminants.

#### CLEANING

Remove as much product as possible from application equipment before cleaning.

Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly.

Some local authorities have special facilities for the disposal of waste coatings.

Do not empty product into drains or watercourses.

## PRECAUTIONS

Keep out of reach of children.

In case of contact with eyes wash immediately with plenty of water.

Seek medical attention/advice.

Remove splashes from skin with soap and water or a recognised hand cleaner.

Protect from freezing. Do not apply paint if there is a risk of heavy rain or frost.

Do not use near fish tanks or ponds.

Every care is taken to ensure that all information provided on this Technical Data Sheet is accurate.

Mould Growth Consultants Ltd. are unable to guarantee results as it has no control over the conditions under which its products are applied.

Before using this product please ensure you have the latest information.

## FINISH AND PACK SIZE

RLT Clearmould First Response Fungicidal Spray 750ml handheld spray bottle.

Approx 7<sup>2</sup>m per 750ml spray bottle of ready to use solution.

## SPREADING RATE

Use a sponge or cloth to apply extending the treatment at least 1 metre in all directions beyond visible signs of mould.

Coverage must not exceed 7 square metres per 750ml of product.

## DRYING TIME

Application will typically be touch dry after 15 – 30 minutes depending on temperature, humidity and airflow.

The surface temperature during application should be between 10°C - 25°C.

Ensure good ventilation during application and drying.

## SHELF LIFE

Under normal and frost-free conditions this product will remain usable for up to two years if stored correctly and unopened.

Store within the temperature range 5°C- 25°C.

PROTECT FROM FROST

## HEALTH AND SAFETY

It is essential that when using any type of chemicals, whether they are disinfectants, washing detergents or mould treatments, that all vulnerable people, children, pets and animals are kept away from the materials and the areas being treated until they are dry. In addition, any spillages of chemicals must be cleaned up immediately before proceeding further with the work.

Store chemical products in a safe place away from children and pets.

Please refer to the Safety, Health and Environmental Information on the container.

Take special precautions during the surface preparation of pre -1960's painted surfaces as they may contain harmful lead.

When preparing the surfaces avoid the inhalation of dust and/or metal particles. Wear a suitable facemask.

Material Safety Data Sheets for this and all other products are freely available from the place of purchase or the address below.

Store in secure dry conditions inaccessible to children, pets or animals.

Containers should be kept closed during storage.

Do not empty into drains, watercourses or access routes to septic tanks.

For further information contact the Sales office on 01372 743334.

## GENERAL INFORMATION

Apply all products in accordance with BS 6150: Code of practice for painting of buildings and BS 8000: Part 12:1989 workmanship on building sites and any additional requirements as detailed in a specification.

All products should be applied in accordance with the Manufacturer's Instructions/Product Data Sheets and Health & Safety requirements.

Inform the Contract Administrator of any discrepancy in specification of coatings and obtain instructions before proceeding with application.

Application of coatings will be taken as joint acceptance by the main contractor and sub-contractor of the suitability of surface and conditions within any given area to receive the specified coatings.

Due to continual changes in the condition of surfaces and substrates, a specification is only current for six months after which time a further inspection may be necessary.

Every care is taken to ensure the information provided is accurate at the time of application. MGC is, however, unable to guarantee results since it has no control over the level of preparation or conditions under which its products are applied.

The information and coverages are given in good faith and are based on our experience and knowledge but without liability.

Please contact MGC Technical Department on 01372 743334 should you have any enquiries regarding this specification.

## TECHNICAL DATA SHEET RLT CLEARMOULD FIRST RESPONSE SPRAY

### MOULD GROWTH CONSULTANTS LIMITED

**Unit A3 Longmead Business Centre, Blenheim Road, Epsom, Surrey KT19 9QQ**

**Tel: 01372 743334    Email: [info@mgcltd.co.uk](mailto:info@mgcltd.co.uk)    Website: [www.mgcltd.co.uk](http://www.mgcltd.co.uk)**